UNCLASSIFIED

AD NUMBER AD152954 CLASSIFICATION CHANGES TO: UNCLASSIFIED FROM: CONFIDENTIAL LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;

Administrative/Operational Use; OCT 1957. Other requests shall be referred to Ballistic Research Labs., Aberdeen Proving Ground, MD.

AUTHORITY

BRL ltr 22 Apr 1981 ; BRL ltr 22 Apr 1981

THIS REPORT HAS BEEN DELIMITED

AND CLEARED FOR PUBLIC RELEADE

UNDER DOD DIRECTIVE 5200.20 AND

NO RESTRICTIONS ARE IMPOSED UPON

ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

UNCLASSIFIED

AD.

Reproduced by the

ARMED SERVICES TECHNICAL INFORMATION AGENCY
ARLINGTON HALL STATION
ARLINGTON 12, VIRGINIA



DOWNGRADED AT 3 YEAR INTERVALS:
DECLASSIFIED AFTER 12 YEARS
DOD DIR 5200.10

UNCLASSIFIED



Armed Services Technical Information Agency

ARLINGTON HALL STATION ARLINGTON 12 VIRGINIA

FOR
MICRO-CARD

CONTROL ONLY

1 OF 1

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SPECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. GOVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OR IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OR PERMISSION TO MANUFACTURE, USE OR SELL ANY PATENTED INVENTION THAT

AD NO. 152954



00052

a



MEMORANDUM REPORT No. 1101 OCTOBER 1957

Drag And Stability Properties
Of A Redstone Warhead Model (U)

L. C. MacALLISTER

DEPARTMENT OF THE ARMY PROJECT No. 5803-03-001

BALLISTIC RESEARCH LABORATORIES



ABERDEEN PROVING GROUND, MARYLAND

CONFIDENTIAL

570

BEST

AVAILABLE

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1101

OCTOBER 1957

DRAG AND STABILITY PROPERTIES OF A REDSTONE WARHEAD MODEL (U)

L. C. MacAllister

Requests for additional copies of this report will be made direct to ASTIA.

Reproduction of this document in whole or in part is prohibited except with permission of the issuing office; however, ASTIA is authorized to reproduce this document for U. S. Government purposes.

Department of the Army Project No. 5B03-03-001 Ordnance Research and Development Project No. TB3-0108

ABERDEEN PROVING GROUND, MARYLAND

CONFIDENTIAL 58AA 570

BALLISTIC RESEARCH LABORATORIES

MEMORANDUM REPORT NO. 1101

ICMacAllister/iw Aberdeen Proving Ground, Md. October 1957

DRAG AND STABILITY PROPERTIES OF A REDSTONE WARHEAD MODEL (U)

ABSTRACT

The drag and stability properties of a Redstone Warhead Model, as determined by range firings, for $0.7 \le M \le 3.5$ are presented.

SMOOLS

Drag coefficient
Static moment derivative (per radian)
Normal force derivative (per radian)
Center of pressure (calibers from base) -
Damping derivative due to angular velocity
Damping derivative due to yawing velocity
reference area = base area
reference length = base diameter (d)

INTRODUCTION

A version of the Redstone missile Warhead was tested in the Transonic Free Flight Range of the Ballistic Research Laboratories at the request of ABMA. The current model (Fig. 1 and 2) differed from earlier models in that the after body was a single conical section instead of a cone section and a cylinder. The models were encased in a plastic sabot (Fig. 2) and launched through the range from a smooth bored five-inch gun. Sixteen models were launched at speeds from 800 to 4000 fps and all tut one model traversed the full range of instrumentation. A summary of the initial firing data and the physical measurements of the model are given in Table I.

RESULTS

The range data were processed by the usual techniques and the reduction and motion parameters are given in Table II. The resulting aerodynamic coefficients are given in Table III.

The drag coefficient, C_D , is shown in Figure 3. The curve shown is for zero yaw. A value of $C_{D_8^2}$ of 2.5 per squared radians has been used to reduce the individual round values to a zero yaw value. This value of $C_{D_8^2}$ seems adequate for the supersonic data.

The moment derivative, C_{M} , (for a center of mass position 2.47 calibers forward of base) is given in Figure 4. Maximum stability occurs at about M=0.9 and decreases with increasing Mach number. In fact, extrapolation would give a neutral point at about M=6; however, the slope of the C_{M} curve may change at speeds above—use tested. The normal force slope is shown in Figure 5 and the center of pressure of the normal force in Figure 6.

The damping moment derivatives, $(C_{m_{\hat{q}}} + C_{m_{\hat{q}}})$, Figure 7, are stabilizing except at high subsonic speeds. For Mach numbers greater than about 1.1 $(C_{m_{\hat{q}}} + C_{m_{\hat{q}}})$ is fairly constant and adequately large.

Representative shadowgraphs of the model in flight are given in Figure 8 to 16. It might be noted that even at the lowest test speed (M = 0.7) small shock waves exist at the corner of the nose cone, hence these data do not represent a fully subsonic local flow state. Also, almost all of the variations of the model's properties, except slow trends, occur in the region from the

lowest speed tested up to about M = 1.2 where full supersonic flow appears to be established over the body and the control vanes.

REMARKS

Normally in the processing of range data from a statically stable symmetric missile which is not spinning and has a linear force system certain equalities of the reduction parameters are preserved. Primarily these are equality in magnitude of the epicyclic rates, b₁ and b₂. It can be noted in Table II that these equalities are not always present to within the probable accuracy of the data. Generally this can be ascribed to three causes:

- 1. Small size of one of the epicyclic modes, a degenerate fitting condition, i.e., rounds 2-4471 and 2-4476. These may be handled by computing the properties utilizing the equalities and the significant mode.
- 2. Small missile asymmetries where impossible, or impractical, to process by asymmetric reduction systems. The highest velocity rounds are most apt, mechanically, to have suffered some slight damage.
- 3. Nonlinearity of the aerodynamic force system. This is partially allowed for but may be the only logical reason why the data for the low Mach number rounds has inconsistent damping for the two modes.

LC Mac Allisten

L. C. MacALLISTER

REFERENCES

1.D-13 358

- 1. Rogers, W. K., The Transonic Free Flight Range, BRL Report No. 889, 1993.
- 2. Rogers, W. K., Free Flight Tests of A Model of The "Redstone", ESSM-A-14,
 Warhead, BRIM 885, 1955.
- 3. Murphy, C. H., Data Reduction for Free Flight Ranges, BRL Report 900, 1956.

TABLE I
Test Conditions

Round Number	Date	Mid Range Test Velocity	Weight	C. G.	Remarks
	1957	fps	16	in. from base	
2-4431	2 March	3450	8.11		
2-4432	2 March	1280	8.08		•
2-4433	2 March	830	8.10	7.413	
2-4470	18 March	1250	8.11	7.422	
2-4471	18 March	1470	8.10	7.515	
2-4472	18 March	1600	8.11	7.420	Hit fragment shield in second group
-4473	18 March	1600	8.10	7.416	in second group
2-4474	20 March	2770	8.08	7.404	
2-4475	20 March	2430	8.09	7.412	
2-4476	20 March	3060	8.09	7.410	
2-4479	27 March	810	8.09	7.414	
2-4480	27 March	810	8.11	7.414	
2-4481	27 March	920	8.10	7.414	
2-4482	28 March	1050	8.10	7.414	
2-4483	28 March	1100	8.09	7.414	
2-4484	28 March	3990	. 8.10	7.413	

Average maximum diameter (20 measurements) = 3.000 (\frac{+.002}{-.001})

Average length (20 measurements) = 14.397 (\frac{+.006}{-.017}in)

Average axial mement of inertia (2 measurements)

Average transverse moment of inertia (2 measurements)


TABLES II
REDUCTION AND MOTION PARAMETERS

Round Number	Mach Number	δ ²		lic Yaw (deg/ft)		Damping (1/ft)			Standa: Yaw Fit	rd Error Swerve Fit	
		(deg^2)	b	b ₂	λ ₁ 10 ³	λ ₂ 10 ³	K	K ₂	rad	feet	
2-4479	.717	11.2	-1.853	1.932	45	05	.0248	.0529	.0030	.020	
2-4480	.720	9.8	-1.909	+1.897	+1.02	47	.0325	.0424	.0048	.041	
2-4481	.814	5.9	-1.999	+2.031	+ .44	+ .32	.0303	.0292	.0029	.020	
2-4482	.921	22.5	°-2.198	+2.17	1.21	+1.40	.0291	.0904	.0045	.0.15	
2-4483	.971.	7.7	-2.031	+2.058	1.10	+1.57	.0210	0394	.0040	,0 5	
2-4470	1.11.0	5.3	-1.865	+1.848	1.65	+1.59	.0260	.0254	.0027	бто.	
2-4471	1.302	1.4	-1.449	+1.785	1.56	+3.96	.0169	.0052	.0020	.016	
2-4473	1.436	15.0	-1.339	+1.371	1.18	+1.64	.0298	.0547	.0042	.031.	
2-4475	2.159	4.1	-1.138	+1.116	1.65	+1.46	.0244	.0212	.0016	.022	
2-4474	2.465	9.4	-1.129	+1.032	1.60	+1.62	.0315	.0325	.0027	.012	
2-4476	2.714	1.2	-1.061	+1.000	2.09	+1.47	.0081	.0156	.0033	.025	
2-4484	3.453	5.0	-0.904	+0.904	2.29	2.29	.0238	.0216	.0058	.061	

TABLE III
AERODYNAMICS COEFFICIENTS


Mach Number	Reynold: Number	s _{δ²}	c_{D}	C _M	$^{\mathrm{C}}$ N $_{oldsymbol{lpha}}$	CP _N	C _{Mq} + C _M	Round Number
	(10 ⁻⁶)	(deg ²)) (per rad		from ba		
.717	1.25	11.2	.2801	-1.668	3.79	2.03	4.1	2-4479
.722	1.26	9.8	.2801	-1.685	3.63	2.01	8.5	2-4480
.737	0		.2758					
.814	1.42	5.9	.2956	-1.890	3.06	1.85	-2.3	2-4481
.921	1.61	22.5	.3998	-2.217	3.44	1.83	-24.5	2-4482
.971	1.70	7.7	.4395	-1.939	5.14	2.09	-20.6	2-4483
1.110	1.93	5.3	.5485	-1.610	4.48	2.11	-30.2	2-4470
1.302	2.27	1.4	.5024	-1.215	4.08	2.17	<u>-59.0</u>	2-4471
1.430	2.51	15.2	. 4966	858	3.32	2.21	-28.0	2-4473
2.159	3.73	4.1	.3845	601	3.46	2.30	-30.9	2-4475
2.465	4.29	9.4	.3456	547	3.28	2.30	-32.2	2-4474
2.714	4.68	1.2	.3163	504	3.86	2.34	-35.1	2-4476
3.05		0	.2872					
3.453	6.02	5.0	.2633	388	2.73	2.33	49.9	2-4484

Underlined values are poorly determined due to small yaw size.



11
CONFIDENTIAL





NOTE: All Dimensions are in Inches

12







FIGURE 2 TYPICAL RANGE MODEL IN SABOT





CONFIDENTIAL





CONFIDENTIAL





CONFIDENTIAL




FIGURE 8 SHADOWGRAPH M = 0.72




FIGURE 9 SHADOWGRAPH M = 0.81




FIGURE 10 SHADOWGRAPH M± 0.92




FIGURE II SHADOWGRAPH M= 0.97




FIGURE 12 SHADOWGRAPH M = 1.11




FIGURE 13 SHADOWGRAPH M = L30

24




FIGURE 14 SHADOWGRAPH M = 1.52




FIGURE 15 SHADOWGRAPH M = 2.16




FIGURE 16 SHADOWGRAPH M = 3.45

PAGE

28

BLANK

100			
No. of Copies	Organization	No. of Copies	Organization
2	Chief of Ordnance Department of the Army Washington 25, D. C. Attn: ORDTB - Bal Sec ORDTU	1	Commanding Officer and Director David W. Taylor Model Basin Washington 7, D. C.
			Attn: Aerodynamics Lab.
10	British Joint Services Mission 1800 K Street, N. W. Washington 6, D. C.	1	Commander Naval Air Development Center Johnsville, Pennsylvania
	Attn: Mr. John Izzard, Reports Officer	1	Commanding Officer Naval Air Rocket Test Station Dover, New Jersey
4	Canadian Army Staff 2450 Massachusetts Ave., N. Washington 8, D. C.	W. 3	Commander Naval Ordnance Test Station
3	Chief, Bureau of Ordnance Department of the Navy Washington 25, D. C. Attn: ReO		China Lake, California Attn: Technical Library Aeroballistics Lab. Code 5034
2	Commander Naval Proving Ground Dahlgren, Virginia	4	Commander Air Research and Development Center P. O. Box 1395 Baltimore 3, Maryland
2	Commander Naval Ordnance Laboratory White Oak	1	Attn: Deputy for Development Commander
	Silver Spring, Maryland Attn: Technical Library	*	Air Force Armament Center Eglin Air Force Base, Florida Attn: ACOT
1	Superintendent Naval Postgraduate School Monterey, California	1	Commander Arnold Engineering Development Center
2	Commander Naval Air Missile Test Center Point Mugu, California		Tullahoma, Tennessee Attn: Deputy Chief of Staff, R&D

No. of Copies		No. of Copies	Organization
10	Director Armed Services Technical Information Agency Document Service Center Knott Building Dayton 2, Ohio Attn: DSC - SD	1	Director, JPL Ord Corps Installation 4800 Oak Grove Drive Department of the Army Pasadena, California Attn: Mr. Irl E. Newlan, Reports Group
2	U. S. Atomic Energy Commission Sandia Corporation P. O. Box 5900 Albuquerque, New Mexico	6	Commanding General Redstone Arsenal Huntsville, Alabama Attn: Technical Library T. G. Reed, ABMA
1	Director National Advisory Committee for Aeronautics 1512 H Street, N. W. Washington 25, D. C.	3	Commanding Officer Picatinny Arsenal Dover, New Jersey Attn: Samuel Feltman Ammunition Lab.
1	Director National Advisory Committee for Aeronautics Ames Laboratory Moffett Field, California	1	Commanding General Frankford Arsenal Philadelphia 37, Pennsylvania Attn: Reports Group
7	Attn: Dr. A. C. Charters Mr. H. J. Allen	1	Commanding Officer Chemical Corps Chemical and Radiological Lab.
3	Director National Advisory Committee		Army Chemical Center, Maryland
	for Aeronautics Langley Memorial Aeronautical Laboratory Langley Field, Virginia Attn: Mr. J. Bird Mr. C. E. Brown	1	Commanding Officer Diamond Ordnance Fuze Laboratories Washington 25, D. C. Attn: ORDTL - 06.33
	Dr. Adolf Busemann	1	The Johns Hopkins University Operations Research Office
1	Director National Advisory Committee for Aeronautics		7100 Connecticut Avenue Chevy Chase, Maryland Washington 15, D. C.
	Lewis Flight Propulsion Lab. Cleveland Airport Cleveland, Ohio Attn: F. K. Moore		Attn: Document Control Office

No. of Copies	Or	ganization	No. of Copies		Organization
2	Tilin	r Research Foundation ois Institute of hnology	1		IR ion of General Dynamics poration
		ology Center			nce Aerophysics Lab.
		go 16, Illinois			erfield, Texas
		Mr. W. Casier Dr. A. Wundheiler			Mr. J. E. Arnold
				THRU:	Bureau of Ordnance
	THRU:	3			Representative
		Chicago Ordnance			Ordnance Aerophysics
		District			Laboratory
		209 W. Jackson Blvd.			Daingerfield, Texas
		Chicago, Illinois	7		
			1		l Electric Company
2		d Physics Laboratory eorgia Avenue			e and Ordnance Systems rtment
		Spring, Maryland		3198 C	hestnut Street
	Attn:	Mr. George L.			elphia, Pennsylvania
		*Seielstad		Attn:	A. M. Smith
	THRU:	Naval Inspector of		THRU:	Commanding Officer
		Ordnance			Philadelphia Ordnance
		Applied Physics Lab.			District
		9621 Georgia Avenue			128 N. Broad Street
		Silver Spring, Marylan	nd		Philadelphia 2, Pa.
		_			Attn: Mr. L. I. Chasen
1.	Aeroph	ysics Development Corp.			
	P. O.	Box 657	1	M. W. 1	Kellogg Company
	Pacifi	c Palisades, California	ı		f Danforth Avenue
				Jersey	City 3, New Jersey
	THRU:	Commanding Officer Los Angeles Ordnance		Attn:	Miss E. M. Hedley
		District		THRU:	Inspector of Naval
	7	55 South Grand Avenue			Material
		Pasadena 1, California	L		Naval Industrial Reserve
					Shipyard
1	Cornel	l Aeronautical Lab., Ir	ic.		Building 24, Port Newark
	4455 G	enesee Street			Newark 5, New Jersey
	Buffalo	o 5, New York			
	Attn:	Miss Elma T. Evans,	1	Ramo-Wo	ooldridge Corporation
		Librarian		5730 Az	rbor Vitae Atreet
				P. O. I	Box 45067 Airport Station
	THRU:	Bureau of Aeronautics Representative		Los Ang	geles 45, California
		P. O. Box 235		THRU:	Los Angeles Air
		Buffalo 21, New York			Procurement District
		Attn: Commander Bolle	es		1206 S. Maple Avenue
					Los Angeles 15, Calif.

No. of Copies	Organization	No. of	On monination
COPIES	Organiza ston	Copies	Organization
1	Research and Advanced Development Division AVCO Manufacturing Corp. 20 South Union Street Lawrence, Massachusetts	1	United Aircraft Cor. on Research Department East Hartford 8, Connecticut Attn: Mr. C. H. King
	Attn: Mr. W. Stevenson		THRU: Bureau of Aeronautics Representative
	THRU: Boston Air Procureme District Boston Army Terminal Boston 10, Massachus		Pratt & Whitney Aircraft United Aircraft Corp. East Hartford 8, Conn.
	boston 10, rassacias	1	Wright Aeronautical Division
1	Technical Documents Service Willow Run Laboratories		Curtiss-Wright Corporation Wood-Ridge, New Jersey
	University of Michigan Willow Run Airport		Attn: Sales Dept. (Government)
	Ypsilanti, Michigan Attn: Mr. J. E. Corey		THRU: Air Force Plant Representative
	THRU: Commander Central Air Procureme	ent	Wright Aeronautical Division Wood-Ridge, New Jersey
	District West Warren & Lonyo A Detroit 32, Michigan	ve. l	Professor George Carrier Division of Applied Sciences Harvard University
1	University of So. California Engineering Center		Cambridge 38, Massachusetts
	Los Angeles 7, California Attn: Mr. H. R. Saffell, Director	1	Professor Clark B. Milliken Guggenheim Aeronautical Iab. California Institute of Technology
	THRU: Bureau of Aeronautics Representative		Pasadena 4, California
	Aeroject Engineering Corporation 6352 North Irvindale Avenue	1	Dr. A. E. Puckett Hughes Aircraft Company Culver City, California
	Azusa, California	1	Dr. L. H. Thomas Watson Scientific Computing
			Laboratory 612 West 116th Street New York 27, New York

No. of Copies	Organization
1	Assistant Secretary of Defense (R&E) The Pentagon Washington 25, D. C.
	Attn: Director, Guided Missiles
2	Chief of Staff Department of the Army
	Washington 25, D. C. Attn: Director, Special Weapons Army Ballistic Missile Committee



Armed Services Technical Information Agency

ARLINGTON HALL STATION ARLINGTON 12 VIRGINIA

FOR MICRO-CARD

CONTROL ONLY

NOTICE: WHEN GOVERNMENT OR OTHER DRAWINGS, SECIFICATIONS OR OTHER DATA ARE USED FOR ANY PURPOSE OTHER THAN IN CONNECTION WITH A DEFINITELY RELATED GOVERNMENT PROCUREMENT OPERATION, THE U. S. COVERNMENT THEREBY INCURS NO RESPONSIBILITY, NOR ANY OBLIGATION WHATSOEVER; AND THE FACT THAT THE GOVERNMENT MAY HAVE FORMULATED, FURNISHED, OF IN ANY WAY SUPPLIED THE SAID DRAWINGS, SPECIFICATIONS, OR OTHER DATA IS NOT TO BE REGARDED BY IMPLICATION OR OTHERWISE AS IN ANY MANNER LICENSING THE HOLDER OR ANY OTHER PERSON OR CORPORATION, OR CONVEYING ANY RIGHTS OF FERMISSION TO MANUFACTURE. USE OR SELL ANY PATENTED INVENTION THAT MAY IN LAY WAY BE RELATED THERETO.



UNCLASSIFIED

UNCLASSIFIED